

	REVISION HISTORY						
REV	DESCRIPTION	DATE	APPROVED				
1							
2							
3							





FORCES (STATICA	FORCES (STATICALLY MEASURED)				
Fì	(F2)				
80 LBS (356 N) +10% -5%					

NOTES:

- 1) MATERIAL: CYLINDER HEAVY GAUGE STEEL, BLACK PAINT. ROD HARDENED STEEL BLACK NITRIDE.
- 2) OPERATING TEMPERATURE: -40°C TO +80°C.
- 3) STANDARD LABEL TO INCLUDE PART NUMBER, DATE CODE AND WARNING MESSAGE. LABEL NOT TO BE REMOVED.
- 4) GAS SPRING NOT TO BE CHANGED OR MODIFIED FROM ITS ORIGINAL MANUFACTURED INTENT.
- 5) GAS SPRING IS SUGGESTED TO BE MOUNTED SHAFT DOWN (ROD DOWN) FOR MAXIMUM PERFORMANCE.
- 6) CONNECTORS TO BE ORIENTED AS SHOWN ±5°.
- 7) GAS SPRINGS WILL BE SEALED IN CLEAR PLASTIC BAGS TO AVOID DAMAGE, DUST, OR OTHER FOREIGN OBJECTS.
- 8) GAS SPRING TO BE ASSEMBLED WITH END FITINGS COMPLETELY FASTENED.
- 9) GAS SPRINGS ARE NOT TO BE OPENED.
- 10) GREASE TO BE INCLUDED INSIDE THE BALL SOCKET OF THE END FITTINGS.

				NAME	DATE
NORI	DRAWN CHECKED	CSH		06/22/2023	
THIS DOCUMENT AND ITS C	PART No.	NSG1480S80		REV	
THIS DOCUMENT CO	TITLE	GAS SPRING			
DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN.		TOLER	ANCES	ICES THIRD ANGLE	
		X.X	± 0.060	PROJECTION	1:1
	ALL DIMENSIONS ARE DUAL UNLESS OTHERWISE SPECIFIED	X.XX	± 0.030		1
REMOVE ALL BURRS AND BREAK		X.XXX	± 0.010		SIZE
ALL SHARP EDGES		ANGLES	± 1°		
		HOLES	± 0.005	SHEET1 OF1	