

	REVISION HIST	ORY	
REV	DESCRIPTION	DATE	APPROVED
1			
2			
3			





FORCES (STATICALLY MEASURED)						
Fì	(F2)					
60 LBS (267 N) +10% -5%						

## **NOTES**:

- 1) MATERIAL: CYLINDER HEAVY GAUGE STEEL, BLACK PAINT. ROD HARDENED STEEL BLACK NITRIDE.
- 2) OPERATING TEMPERATURE: -40°C TO +80°C.
- 3) STANDARD LABEL TO INCLUDE PART NUMBER, DATE CODE AND WARNING MESSAGE. LABEL NOT TO BE REMOVED.
- 4) GAS SPRING NOT TO BE CHANGED OR MODIFIED FROM ITS ORIGINAL MANUFACTURED INTENT.
- 5) GAS SPRING IS SUGGESTED TO BE MOUNTED SHAFT DOWN (ROD DOWN) FOR MAXIMUM PERFORMANCE.
- 6) CONNECTORS TO BE ORIENTED AS SHOWN ±5°.
- 7) GAS SPRINGS WILL BE SEALED IN CLEAR PLASTIC BAGS TO AVOID DAMAGE, DUST, OR OTHER FOREIGN OBJECTS.
- 8) GAS SPRING TO BE ASSEMBLED WITH END FITINGS COMPLETELY FASTENED.
- 9) GAS SPRINGS ARE NOT TO BE OPENED.
- 10) GREASE TO BE INCLUDED INSIDE THE BALL SOCKET OF THE END FITTINGS.

				NAME	DATE
NOR	DRAWN CHECKED	CSH		06/22/2023	
THIS DOCUMENT AND ITS C	PART No.	NSG1500S60MT1		REV	
THIS DOCUMENT CC PROPRIETARY INFORMA	TITLE	GAS SPRING			
DISTRIBUTION, UTILISATION OF THIS DOCUMENT OR A	TOLERANCES		THIRD ANGLE	SCALE	
EXPRESS AUTHORISATION	X.X	± 0.060	PROJECTION	1:1	
	ALL DIMENSIONS ARE  DUAL  UNLESS OTHERWISE  SPECIFIED	X.XX	± 0.030		1
REMOVE ALL BURRS AND BREAK		X.XXX	± 0.010		SIZE
ALL SHARP EDGES		ANGLES	± 1°		
		HOLES	± 0.005	SHEET 1 OF 1	