



REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED



- NOTES
1. MATERIAL: CYLINDER - HEAVY GAUGE STEEL, BLACK PAINT. ROD - HARDENED STEEL BLACK NITRIDE
 2. FORCE: 70LBS/ 311N
 3. Drawing lengths (not dimensioned) of cylinder and rod bodies are not to scale
 4. Operating temperature: -30°C TO +80°C
 - 5 Standard label to include part number, date code, and warning message. Label not to be removed
 6. Gas Spring not to be modified, or changed from manufactured, original, product
 7. Gas Spring is suggested to be mounted shaft down (rod down) for maximum performance
 8. Gas Springs will be individually packed in sealed clear plastic bags, to avoid damage, dust, or other foreign material objects
 9. Gas Springs are not to be opened

NORMONT	DRAWN	NAME	DATE	
	CHECKED	FAITH	10/26/22	
<small>THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NUOMENG. THIS DOCUMENT CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION. THE REPRODUCTION, DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN.</small>	DWG NO		REV	
	NSG1968S70		0	
	TITLE			
<small>REMOVE ALL BURRS & BREAK ALL SHARP EDGES</small>	ALL DIMENSIONS ARE IN		<small>THIRD ANGLE PROJECTION</small> 	
	Inch			SCALE
	UNLESS OTHERWISE SPECIFIED			N.T.S.
				SIZE
	TOLERANCES	SHEET 1 OF 1		
	X.X ± 0.060			
	X.XX ± 0.030			
	X.XXX ± 0.015			
	ANGLES ± FE			
	HOLES ± 0.005			