



REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
1			
2			
3			



FORCES (STATICALLY MEASURED)	
F1	(F2)
90 LBS (400 N) $+10\%$ -5%	

- NOTES:
- 1) MATERIAL: CYLINDER - HEAVY GAUGE STEEL, BLACK PAINT. ROD - HARDENED STEEL BLACK NITRIDE.
 - 2) OPERATING TEMPERATURE: -40°C TO +80°C.
 - 3) STANDARD LABEL TO INCLUDE PART NUMBER, DATE CODE AND WARNING MESSAGE. LABEL NOT TO BE REMOVED.
 - 4) GAS SPRING NOT TO BE CHANGED OR MODIFIED FROM ITS ORIGINAL MANUFACTURED INTENT.
 - 5) GAS SPRING IS SUGGESTED TO BE MOUNTED SHAFT DOWN (ROD DOWN) FOR MAXIMUM PERFORMANCE.
 - 6) CONNECTORS TO BE ORIENTED AS SHOWN $\pm 5^\circ$.
 - 7) GAS SPRINGS WILL BE SEALED IN CLEAR PLASTIC BAGS TO AVOID DAMAGE, DUST, OR OTHER FOREIGN OBJECTS.
 - 8) GAS SPRING TO BE ASSEMBLED WITH END FITINGS COMPLETELY FASTENED.
 - 9) GAS SPRINGS ARE NOT TO BE OPENED.
 - 10) GREASE TO BE INCLUDED INSIDE THE BALL SOCKET OF THE END FITTINGS.

<div>NORMONT</div>			NAME	DATE	
		DRAWN	CSH	08/22/2023	
		CHECKED			
<div>THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NORMONT</div> <div>THIS DOCUMENT CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION. THE REPRODUCTION, DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN.</div>		PART No.		REV	
		NSG2000S90			
		TITLE			GAS SPRING
<div>REMOVE ALL BURRS AND BREAK ALL SHARP EDGES</div> <div>ALL DIMENSIONS ARE DUAL UNLESS OTHERWISE SPECIFIED</div>		TOLERANCES		THIRD ANGLE PROJECTION	SCALE
		X.X	± 0.060		1:1
		X.XX	± 0.030		
		X.XXX	± 0.010		
		ANGLES	± 1°	SIZE	
		HOLES	± 0.005		D
		SHEET 1 OF 1			