




REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED



- NOTES**
1. MATERIAL : CYLINDER - HEAVY GAUGE STEEL , BLACK POWDERCOAT PAINT  
ROD - HARDENED STEEL BLACK NITRIDE
  2. FORCE :30LBS/133.5N
  3. DIMENSIONS ASSUMING END CONNECTORS ARE FULLY SCREWED INTO PLACE
  4. DRAWING LENGTHS ( NOT DIMENSIONED ) OF CYLINDER AND ROD BODIES ARE NOT TO SCALE
  5. OPERARTING TEMPERATURE : - 3 0 C TO + 8 0 C
  6. Label to include part number , date code , and waming message Label not to be remove
  7. Gas Spring not to be modified , or changed from manufactured , original , product
  8. Gas Spring to is suggested to be mounted shaft down ( rod down ) for maximum performance
  9. Connectors to be lined up per drawing . 5 degree deviation permitted
  10. Gas Springs will be individually packed in sealed clear plastic bags , to avoid damage , dust , or other foreign material - obiects
  11. Gas Spring to be assembled per the drawing with end fittings assembled / fastened
  12. Gas Springs are not to be opened
  13. Inside of each end fitting to be greased

	DRAWN	NAME	DATE
	CHECKED	Allen	12/13/19
<small>THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NUOMENG. THIS DOCUMENT CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION. THE REPRODUCTION, DISTRIBUTION, UTILIZATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORIZATION IS STRICTLY FORBIDDEN.</small>	DWG NO		REV
	NSG750S30PC1		0
TITLE			
Gas Spring			
<small>REMOVE ALL BURRS &amp; BREAK ALL SHARP EDGES</small>	TOLERANCES		THIRD ANGLE PROJECTION
	XX	±0.060	
	XX.XX	±0.030	
	XX.XXX	±0.015	
ANGLES		SCALE	
±1.0°			N.T.S.
ALL DIMENSIONS ARE IN		SIZE	
inch		B	
UNLESS OTHERWISE SPECIFIED		SHEET 1 OF 1	