


REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED



NOTES

- 1 . MATERIAL : CYLINDER - HEAVY GAUGE STEEL , BLACK POWDERCOAT PAINT
ROD - HARDENED STEEL BLACK NITRIDE
- 2 . FORCE :50LBS/222.5N
- 3 . DIMENSIONS ASSUMING END CONNECTORS ARE FULLY SCREWED INTO PLACE
- 4 . DRAWING LENGTHS (NOT DIMENSIONED) OF CYLINDER AND ROD BODIES ARE NOT TO SCALE
- 5 . OPERATING TEMPERATURE : - 3 0 C TO + 8 0 C
- 6 . Label to include part number , date code , and warning message Label not to be remove
- 7 . Gas Spring not to be modified , or changed from manufactured , original , product
- 8 . Gas Spring to is suggested to be mounted shaft down (rod down) for maximum performance
- 9 . Connectors to be lined up per drawing . 5 degree deviation permitted
- 10 . Gas Springs will be individually packed in sealed clear plastic bags , to avoid damage , dust , or other foreign material - objects
- 11 . Gas Spring to be assembled per the drawing with end fittings assembled / fastened
- 12 . Gas Springs are not to be opened
- 13 . Inside of each end fitting to be greased



THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NUOMENG
THIS DOCUMENT CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION. THE REPRODUCTION, DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORIZATION IS STRICTLY FORBIDDEN.

DRAWN	NAME Allen	DATE 12/13/19
CHECKED		
DWG NO NSG960S50PC1	REV 0	
TITLE Gas Spring		
TOLERANCES X.X ±0.060 X.XX ±0.030 X.XXX ±0.015 ANGLES ±1.0° HOLES ±0.005	THIRD ANGLE PROJECTION 	SCALE N.T.S. SIZE B
REMOVE ALL BURRS & BREAK ALL SHARP EDGES	ALL DIMENSIONS ARE IN inch UNLESS OTHERWISE SPECIFIED	SHEET 1 OF 1