

## NOTES:

1) MATERIAL: CYLINDER - STEEL, BLACK PAINT / ROD - STEEL BLACK NITRIDE.

2) OPERATING TEMPERATURE: -40°C TO +80°C.

3) STANDARD PART IDENTIFICATION TO INCLUDE PART NUMBER, DATE CODE AND WARNING MESSAGE. LABEL NOT TO BE REMOVED

4) GAS SPRING IS SUGGESTED TO BE MOUNTED SHAFT DOWN (ROD DOWN) FOR MAXIMUM PERFORMANCE.

5) END FITTINGS TO BE ORIENTED AS SHOWN ±5°.

6) GAS SPRINGS WILL BE SEALED IN CLEAR PLASTIC BAGS TO AVOID DAMAGE, DUST, OR OTHER FOREIGN OBJECTS.

7) GAS SPRING TO BE ASSEMBLED WITH END FITTINGS COMPLETELY FASTENED.

8) GREASE TO BE INCLUDED INSIDE THE BALL SOCKET OF THE END FITTINGS.

		REVISION HISTORY					
	F	REV DESC	RIPTION		DATE	APPROVED	
ΞN	DED						
	-( 145 [ 5.71 ] ) МАХ	(ТИВЕ ———					
	\ [ ]./ ]/						
	4						
		·			<b></b> -		
				ſ			
	φ 18 [.7]]						
					NAME	DATE	
	NORMONT		DRAWN		JACN	01/10/2024	
			CHECKED				
	THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NORMONT THIS DOCUMENT CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION. THE REPRODUCTION, DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN.		PART No. NSG1094M20		REV -		
L			TITLE GAS SPRING				
L			TOLERANCES		THIRD ANG	F SCALE	
			X.X	± 0.060	PROJECTIO		
				± 0.030			
	REMOVE ALL BURRS AND BREAK ALL SHARP EDGES	ALL DIMENSIONS ARE	X.XX	1	(+)+		
			X.XX X.XXX	± 0.010		SIZE	
		DUAL UNLESS OTHERWISE		± 0.010 ± 1°		SIZE	
			X.XXX		SHEET 1 OF		