

REVISION HISTORY					
REV	DESCRIPTION	DATE	APPROVED		





FORCES (STATICALLY MEASURED)						
Fl	(F2)					
120 LBS (120 N) ^{+7%} _{-5%}	-					

NOTES:

- 1) MATERIAL: CYLINDER STEEL, BLACK PAINT / ROD STEEL BLACK NITRIDE.
- 2) OPERATING TEMPERATURE: -40°C TO +80°C.
- 3) STANDARD PART IDENTIFICATION TO INCLUDE PART NUMBER, DATE CODE AND WARNING MESSAGE. LABEL NOT TO BE REMOVED
- 4) GAS SPRING IS SUGGESTED TO BE MOUNTED SHAFT DOWN (ROD DOWN) FOR MAXIMUM PERFORMANCE.
- 5) END FITTINGS TO BE ORIENTED AS SHOWN ±5°.
- 6) GAS SPRINGS WILL BE SEALED IN CLEAR PLASTIC BAGS TO AVOID DAMAGE, DUST, OR OTHER FOREIGN OBJECTS.
- 7) GAS SPRING TO BE ASSEMBLED WITH END FITTINGS COMPLETELY FASTENED.
- 8) GREASE TO BE INCLUDED INSIDE THE BALL SOCKET OF THE END FITTINGS.

		NAME		DATE		
NORI	DRAWN		JACN		01/15/2024	
	CHECKED					
THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF NORMONT		PART No.	NSG	NSG12.00M120		REV -
THIS DOCUMENT CC PROPRIETARY INFORMA	TITLE	GAS SPRING				
DISTRIBUTION, UTILISATION OR THE COMMUNICATION OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN.		TOLERANCES		THIRD ANGLE		SCALE
		X.X	± 0.060	PROJECTION		N.T.S
	ALL DIMENSIONS ARE AK DUAL UNLESS OTHERWISE SPECIFIED	X.XX	± 0.030		1	1 11.1.0
REMOVE ALL BURRS AND BREAK		X.XXX	± 0.010		<u> </u>	SIZE
ALL SHARP EDGES		ANGLES	± 1°			C
	5, 26, 12,	HOLES	± 0.005	SHEET1 OF1		