

|     | REVISION HISTORY                         |            |          |  |  |  |  |
|-----|--|------------|----------|--|--|--|--|
| REV | DESCRIPTION                              | DATE       | APPROVED |  |  |  |  |
| 1   | TEMPLATE UPDATED. FORCE TOLERANCE ADDED. | 02/01/2024 | JACN     |  |  |  |  |





| FORCES (STATICALLY MEASURED)                    |      |  |  |  |  |
|---|------|--|--|--|--|
| FI  | (F2) |  |  |  |  |
| 40 LBS (178 N) <sup>+ 10%</sup> <sub>- 5%</sub> | -    |  |  |  |  |

## NOTES:

- 1) MATERIAL: CYLINDER STEEL, BLACK PAINT / ROD STEEL BLACK NITRIDE.
- 2) OPERATING TEMPERATURE: -40°C TO +80°C.
- 3) STANDARD PART IDENTIFICATION TO INCLUDE PART NUMBER, DATE CODE AND WARNING MESSAGE. LABEL NOT TO BE REMOVED.
- 4) GAS SPRING IS SUGGESTED TO BE MOUNTED SHAFT DOWN (ROD DOWN) FOR MAXIMUM PERFORMANCE.
- 5) END FITTINGS TO BE ORIENTED AS SHOWN ±5°.
- 6) GAS SPRINGS WILL BE SEALED IN CLEAR PLASTIC BAGS TO AVOID DAMAGE, DUST, OR OTHER FOREIGN OBJECTS.
- 7) GAS SPRING TO BE ASSEMBLED WITH END FITTINGS COMPLETELY FASTENED.
- 8) GREASE TO BE INCLUDED INSIDE THE BALL SOCKET OF THE END FITTINGS.

|  |   | NAME         |             | DATE         |       |      |
|--|---|--------------|-------------|--------------|-------|------|
| NORI   | DRAWN   | CSH          |             | 05/17/2023   |       |      |
|  |   | CHECKED      |             |              |       |      |
| THIS DOCUMENT AND ITS O  | PART No.  | NSG750M40PC1 |             |              | REV   |      |
| THIS DOCUMENT CO   | TITLE GAS SPRING                                      |              |             |              |       |      |
| DISTRIBUTION, UTILISATION  | TOLERANCES  |              | THIRD ANGLE |              | SCALE |      |
| OF THIS DOCUMENT OR ANY PART THEREOF, WITHOUT EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN. |   | X.X          | ± 0.060     | PROJECTION   |       | 2:1  |
| REMOVE ALL<br>BURRS AND BREAK<br>ALL SHARP<br>EDGES  | ALL DIMENSIONS ARE  DUAL  UNLESS OTHERWISE  SPECIFIED | X.XX         | ± 0.030     |              | 1     |      |
|  |   | X.XXX        | ± 0.010     |              |       | SIZE |
|  |   | ANGLES       | ± 1°        |              |       | C    |
|  |   | HOLES        | ± 0.005     | SHEET 1 OF 1 |       |      |