

	REVISION HISTORY							
REV	DESCRIPTION	DATE	APPROVED					
1	TEMPLATE UPDATED. FORCE TOLERANCE ADDED.	09/01/24	JACN					





FORCES (STATICALLY MEASURED)						
Fl	(F2)					
90 LBS (400 N) ^{+ 10%} _{- 5%}	-					

NOTES:

- 1) MATERIAL: CYLINDER STEEL, BLACK PAINT / ROD STEEL BLACK NITRIDE.
- 2) OPERATING TEMPERATURE: -40°C TO +80°C.
- 3) STANDARD PART IDENTIFICATION TO INCLUDE PART NUMBER, DATE CODE AND WARNING MESSAGE. LABEL NOT TO BE REMOVED
- 4) GAS SPRING IS SUGGESTED TO BE MOUNTED SHAFT DOWN (ROD DOWN) FOR MAXIMUM PERFORMANCE.
- 5) END FITTINGS TO BE ORIENTED AS SHOWN ±5°.
- 6) GAS SPRINGS WILL BE SEALED IN CLEAR PLASTIC BAGS TO AVOID DAMAGE, DUST, OR OTHER FOREIGN OBJECTS.
- 7) GAS SPRING TO BE ASSEMBLED WITH END FITTINGS COMPLETELY FASTENED.
- 8) GREASE TO BE INCLUDED INSIDE THE BALL SOCKET OF THE END FITTINGS.

		NAME		DATE		
NORI	DRAWN CHECKED		CSH		05/17/2023	
THIS DOCUMENT AND ITS C	PART No.	NSG9	NSG960M90MTI			
THIS DOCUMENT CO	TITLE	TITLE GAS SPRING				
DISTRIBUTION, UTILISATION OF THIS DOCUMENT OR A	TOLERANCES		THIRD ANGLE		SCALE	
EXPRESS AUTHORISATION IS STRICTLY FORBIDDEN.		X.X	± 0.060	PROJECTION		2:1
REMOVE ALL BURRS AND BREAK ALL SHARP EDGES	ALL DIMENSIONS ARE DUAL UNLESS OTHERWISE SPECIFIED	X.XX	± 0.030		1	
		X.XXX	± 0.010		Ţ [SIZE
		ANGLES	± 1°			C
		HOLES	± 0.005	SHEET 1 OF 1		